

ELEKTRA Heating Cables

Double-side power supply
VC 10, VC 15, VC 20

ELEKTRA VC Heating Cables are ready-to-install heating sets which are produced in accordance with IEC 800. Heating cable of the length depending on the model, has factory connected cold tail cable.

Typical use:

VC 10 - floor heating (installation in mortar), antifrost protection of pipes.

VC 15 - floor heating (installation in mortar), antifrost protection of gutters and downpipes.

VC 20 - floor heating (installation in mortar), protection against snow and ice of external surfaces e.g. driveways, walkways, ramps, etc.



This package contains:

- ELEKTRA heating cable (on a spool),
- instruction manual.

> Technical data:

Power output:	10, 15 or 20 W/m
Power supply:	230 V ~
Diameter of cable:	~ 5 mm
Min. installation temperature:	+5°C
Max. working temperature:	+80°C
Conduit cables:	2 x 2,5 m; 2 x 1,5 mm ² or 2 x 2,5 mm ²
Type of heating cable:	one-core, conductor screen, double-side power supply
Insulation:	XLPE
Outer sheath:	heat and UV resistant PVC
Resistance tolerance:	±5%
Min. radius of bending cable:	3,5 D
Product certificates:	B, GOST-R
Certificate of ISO 9001:	IQ NET, PCBC
Product mark:	CE



10 W/m

TYPE	LENGTH	POWER
-	m	W
VC 10/70	7	70
VC 10/95	10	95
VC 10/120	12	120
VC 10/145	15	145
VC 10/180	18	180
VC 10/230	23	230
VC 10/280	28	280
VC 10/320	32	320
VC 10/370	37	370
VC 10/440	44	440
VC 10/510	51	510
VC 10/580	58	580
VC 10/640	64	640
VC 10/780	78	780
VC 10/1010	101	1010
VC 10/1270	127	1270
VC 10/1550	155	1550
VC 10/1730	173	1730
VC 10/2080	208	2080
VC 10/2200	220	2200
VC 10/2450	245	2450
VC 10/2690	269	2690
VC 10/2940	294	2940
VC 10/3180	318	3180

15 W/m

TYPE	LENGTH	POWER
-	m	W
VC 15/90	6	90
VC 15/120	8	120
VC 15/150	10	150
VC 15/180	12	180
VC 15/220	15	220
VC 15/285	19	285
VC 15/345	23	345
VC 15/390	26	390
VC 15/450	30	450
VC 15/540	36	540
VC 15/630	42	630
VC 15/720	48	720
VC 15/795	53	795
VC 15/960	64	960
VC 15/1240	83	1240
VC 15/1560	104	1560
VC 15/1900	127	1900
VC 15/2110	141	2110
VC 15/2550	170	2550
VC 15/2700	180	2700
VC 15/3000	200	3000
VC 15/3300	220	3300
VC 15/3600	240	3600
VC 15/3900	260	3900

20 W/m

TYPE	LENGTH	POWER
-	m	W
VC 20/100	5	100
VC 20/140	7	140
VC 20/170	9	170
VC 20/205	10	205
VC 20/255	13	255
VC 20/320	16	320
VC 20/400	20	400
VC 20/460	23	460
VC 20/520	26	520
VC 20/620	31	620
VC 20/720	36	720
VC 20/820	41	820
VC 20/920	46	920
VC 20/1100	55	1100
VC 20/1420	71	1420
VC 20/1800	90	1800
VC 20/2200	110	2200
VC 20/2460	123	2460
VC 20/2920	146	2920
VC 20/3120	156	3120
VC 20/3460	173	3460
VC 20/3800	190	3800
VC 20/4140	207	4140
VC 20/4500	225	4500

ATTENTION: Values shown in the table may vary by up to 5%.

> Accessories:

Temperature controllers - page 27-37

Installation accessories - page 24